

KEY FEATURES

- High power handling: 600 W program power
- 2,5" / 1,75" voice coil (LF/HF)
- High sensitivity: 96,5 dB
- FEA optimized common magnet circuit
- Designed with MMSS technology
- Shorting cap for extended response
- Waterproof cone with treatment for both sides of the cone
- PM4 diaphragm for natural sound
- 60° conical coverage horn

TECHNICAL SPECIFICATIONS

Nominal diameter	250 mm	10 in
Rated impedance (LF/HF)	8 / 16 Ω	
Minimum impedance (LF/HF)	5,6 / 10,1 Ω	
Power capacity* (LF/HF)	300 / 50 W _{AES}	
Program power (LF/HF)	600 / 100 W	
Sensitivity (LF/HF**)	96,5 / 104 dB @ 1W @ 1m	
Frequency range	@ Z _N	
Recomended crossover	50 - 20.000 Hz 2 kHz or higher	
Voice coil diameter (LF/HF)	(12 dB/oct min slope) 63,5 mm 2,5 in	
Air gap height	44,45 mm	1,75 in
Voice coil length	10 mm	
Bl factor	17,5 mm	
Moving mass	11,9 N/A	
X_{damage} (peak to peak)	0,036 kg	

MOUNTING INFORMATION

Overall diameter	260,5 mm	10,26 in
Bolt circle diameter	243,5 mm	9,59 in
Baffle cutout diameter	228 mm	8,98 in
Depth	153 mm	6,02 in
Net weight	5,1 kg	11,24 lb

Notes:

* The power capacity is determined according to AES2-1984 (r2003) standard. Program power is defined as the transducer's ability to handle normal music program material.

** Sensitivity was measured at 1m distance, on axis, with 1W input, averaged in the range 1 - 8 kHz.

*** T-S parameters are measured after an exercise period using a preconditioning power test. The measurements are carried out with a velocity-current laser transducer and will reflect the long term parameters (once the loudspeaker has been working for a short period of time).


**** The X_{max} is calculated as (L_{vc} - H_{ag})/2 + (H_{ag}/3,5), where L_{vc} is the voice coil length and H_{ag} is the air gap height.




THIELE-SMALL PARAMETERS***

Resonant frequency, f_s	52 Hz
D.C. Voice coil resistance, R_e	5,1 Ω
Mechanical Quality Factor, Q_{ms}	3,3
Electrical Quality Factor, Q_{es}	0,43
Total Quality Factor, Q_{ts}	0,38
Equivalent Air Volume to C_{ms}, V_{as}	52,3 l
Mechanical Compliance, C_{ms}	256 μm / N
Mechanical Resistance, R_{ms}	3,6 kg / s
Efficiency, η₀	1,7 %
Effective Surface Area, S_d	0,038 m ²
Maximum Displacement, X_{max} ****	6,6 mm
Voice Coil Inductance, L_e	0,36 mH

FREE IMPEDANCE CURVE



FREQUENCY RESPONSE



Note: On axis frequency response measured with loudspeaker standing on infinite baffle in anechoic chamber, 1W @ 1m