



Silver Gold Cap More resolution, more sound stage. Lots of dynamics. Fast reaction, life feeling and natural sound.

Product prescription for JANTZEN Silver Gold Z-cap

Technical Specifications:

- 1 Silver/Gold Metallized Polypropylene
- 2 Metallisation 99% Silver and 1% Gold
- 3 Non inductive construction
- 4 Range 0.01uF to 10uF
- 5 Tolerance +/-2%
- 6 Loss factor 1K 0.00002 10K 0.00001
- 7 Dielectric strength 1200VDC 800VDC 250VDC

Silver Gold Z-cap dimensions:

- | | |
|--------|------------------|
| 0.1uf | =43,5mm x 16,5mm |
| 0.22uf | =45,5mm x 22,5mm |
| 0.33uf | =45,5mm x 25,5mm |
| 0.47uf | =43,5mm x 16,5mm |
| 0.68uf | =43,5mm x 16,5mm |
| 0.82uf | =43,5mm x 18,5mm |
| 1.0uf | =43,5mm x 18,5mm |
| 2.2uf | =45,5mm x 25,5mm |
| 2.7uf | =45,5mm x 31,5mm |
| 3.3uf | =45,5mm x 22,5mm |
| 3.9uf | =45,5mm x 26,5mm |
| 4.7uf | =45,5mm x 26,5mm |