





Product Features:

- High efficiency 12" Mid-Bass
- Smooth frequency response up to 3000 Hz
- 2,5 inch voice coil, kapton former
- Ideal for two way bass reflex systems



Frequency response curve of the loudspeaker taken in a hemispherical, free field environment and mounted in a closed box with an internal volume of 600 liters (21.2 cu. ft.) enclosing the rear of the driver. The impedance magnitude curve is measured in free air.



2nd and 3rd harmonic distortion levels have been raised 20dB. Measurements made at 10% of rated power.

MODEL L12/854K **CODE** 111.40.030

General Specifications

Nominal Diameter	300/11,8	mm/inch
Rated Impedance	8	Ω
Power handling capacity ⁽¹⁾	350	Watts
Program Power ⁽²⁾	700	Watts
Sensitivity 1W, 1m ⁽³⁾	100	dB
Frequency Range	66 - 4000	Hz
Effective Piston Diameter	260/10,2	mm/inch
Maximum Excursion Before Damage (peak to peak)	30/1,2	mm/inch
Minimum Impedance	6,3	Ω
Voice Coil Diameter	64/3	mm/inch
Voice Coil Material	Copper	
Voice Coil Winding Depth	10/0,4	mm/inch
Number of layers	2	
Kind of layer	Outside	
Thickness Top Plate Depth	8/0,3	mm/inch

Thiele - Small Parameters ⁴

Resonance frequency	F _s	67	Hz
DC resistance	R _e	5	Ω
Mechanical factor	Q _{ms}	3,4	
Electrical factor	Q _{es}	0,43	
Total factor	Q _{ts}	0,38	
BL Factor	BL	13,7	T x m
Effective Moving Mass	M _{ms}	38	gr
Equivalent C _{as} air load	V _{as}	58	liters
Effective piston area	S _d	0,053	m ²
Max. linear excursion	X _{max}	3,0	mm
Voice - coil inductance @ 1KHz	L _{e1k}	1,1	mH
Half-space efficiency	Eff	3,91	%

Mounting Information

Overall Diameter	320/12,6	mm/inch
Bolt Circle Diameter	300	mm
Bolt Hole Diameter	7/0,3	mm/inch

Baffle Cutout Diameter

Front Mount	286/11,3	mm/inch
Rear Mount	284/11,2	mm/inch
Depth	137/5,4	mm/inch
Volume occupied by the Driver	2,20/0,1	liters/ft ³
Net Weight	5,40/11,9	Kg/lbs.
Shipping Weight	5,90/13,0	Kg/lbs.

Notes to Specifications

- 1 AES standard (60 - 600) Hz
- 2 Program power is defined as 3dB greater than the nominal rating.
- 3 Sensitivity measurement is based on a 100-500Hz pink noise signal with input power of 2.83V @ 8 Ohms.
- 4 Thiele-Small parameters are measured after a 2 hour warm up period running the loudspeaker at full power handling capacity.