

# HX 160

90 Watt max


8  $\Omega$

Ø 165 mm / 6,5"

## FULL RANGE

Membrana in cellulosa, sospensione in tela smorzata, magnete in neodimio schermato

Paper cone, doped fabric surround, neodymium shielded magnet



Potenza nominale	<b>40 W</b>
Impedenza nominale	<b>8 <math>\Omega</math></b>
Sensibilità (1W/1m)	<b>95 dB</b>
Ø bobina mobile	<b>25 mm</b>
Altezza traferro	<b>4 mm</b>
Fori di fissaggio	<b>6 <math>\varnothing 4,5</math> / <math>\varnothing 167</math></b>
Foro pannello	<b>145 mm</b>

Re	<b>5,36 <math>\Omega</math></b>	D	<b>131 mm</b>
Fs	<b>70,2 Hz</b>	Vas	<b>16 dm<sup>3</sup></b>
Qms	<b>5,14</b>	BxI	<b>6,56 Wb/m</b>
Qes	<b>0,45</b>	Xmax	<b>1,75 mm</b>
Qts	<b>0,42</b>	$\eta^\circ$	<b>1,18 %</b>
Mms	<b>8,25 g</b>	Le	<b>0,17 mH</b>
Cms	<b>0,62 mm/N</b>	Peso	<b>1,14 Kg</b>

