


# MT 200

100 Watt max | 8  $\Omega$  |  $\varnothing$  20 mm



## TWEETER

Soft dome in poliammide, magnete schermato  
Polyamide soft dome, magnetic shielding

Potenza nominale	<b>50 W</b>	Re	<b>5,6 <math>\Omega</math></b>	D	<b>23 mm</b>
Impedenza nominale	<b>8 <math>\Omega</math></b>	Fs	<b>1,1 kHz</b>	Vas	<b>0,002 dm<sup>3</sup></b>
Sensibilità (1W/1m)	<b>90 dB</b>	Qms	<b>6,54</b>	Bxl	<b>2,48 Wb/m</b>
$\varnothing$ bobina mobile	<b>20 mm</b>	Qes	<b>1,32</b>	Xmax	-
Altezza traferro	<b>2 mm</b>	Qts	<b>1,1</b>	$\eta_o$	<b>0,24 %</b>
Fori di fissaggio	<b>4 <math>\varnothing</math> 4 / <math>\varnothing</math> 81</b>	Mms	<b>0,2 g</b>	Le	<b>0,05 mH</b>
Foro pannello	<b>70 mm</b>	Cms	<b>0,01 mm/N</b>	Peso	<b>0,31 Kg</b>



48x30 cm

