

## SPECIFICATION

Nominal Basket Diameter	6.50", 165.10mm
Nominal Impedance*	8 ohms
Power Rating**	100W
Resonance	406.98Hz
Usable Frequency Range***	400Hz-5kHz
Sensitivity	97.8
Magnet Weight	16 oz.
Gap Height	0.25", 6.35mm
Voice Coil Diameter	1.50", 38.10mm

## THIELE & SMALL PARAMETERS

Resonant Frequency (fs)	406.98Hz
DC Resistance (Re)	5.26
Coil Inductance (Le)	0.38mH
Mechanical Q (Qms)	6.04
Electromagnetic Q (Qes)	1.74
Total Q (Qts)	1.35
Compliance Equivalent Volume (Vas)	0.45 liters / 0.02 cu.ft.
Peak Diaphragm Displacement Volume (Vd)	19.01cc
Mechanical Compliance of Suspension (Cms)	0.02mm/N
BL Product (BL)	7.86 T-M
Diaphragm Mass inc. Airload (Mms)	8.00 grams
Efficiency Bandwidth Product (EBP)	233.69
Maximum Linear Excursion (Xmax)	1.50mm
Surface Area of Cone (Sd)	126.70 cm <sup>2</sup>
Maximum Mechanical Limit (Xlim)	3.00mm

## MOUNTING INFORMATION

Recommended Enclosure Volume	
Sealed	N/A
Vented	N/A
Overall Diameter	6.59", 167.39mm
Baffle Hole Diameter	5.69", 144.53mm
Front Sealing Gasket	Fitted as standard
Rear Sealing Gasket	Fitted as standard
Mounting Holes Diameter	0.23", 5.84mm
Mounting Holes B.C.D.	6.06", 153.92mm
Depth	2.20", 55.88mm
Net Weight	3.70 lbs., 1.68 kg
Shipping Weight	4.40 lbs., 2 kg

## MATERIALS OF CONSTRUCTION


Copper voice coil  
 Polyimide former  
 Ferrite magnet  
 Non-vented core  
 Pressed steel basket  
 Paper Cone  
 Cloth cone edge  
 Solid composition paper dust cap

  
**EMINENCE®**  
 The Art and Science of Sound



## ALPHA-6CBMRA AMERICAN STANDARD SERIES

Recommended for pro audio, car audio, and bass guitar midrange applications. Sealed basket affords this speaker enclosure independence.



\* Please inquire about alternative impedances.

\*\* Multiple units exceed published rating evaluated under EIA 426A noise source and test standard while in a free-air, non-temperature controlled environment.

\*\*\* The average output across the usable frequency range when applying 1W/1M into the nominal impedance. ie: 2.83V/8ohms, 4V/16ohms.

Eminence response curves are measured under the following conditions: All speakers are tested at 1w/1m using a variety of test set-ups for the appropriate impedance | LMS using 0.25" supplied microphone (software calibrated) mounted 1m from wall/baffle | 2ft. X 2ft. baffle is built into the wall with the speaker mounted flush against a steel ring for minimum diffraction | Hafler P1500 Trans-Nova amplifier | 2700 cu.ft. chamber with fiberglass on all six surfaces (three with custom-made wedges)