



12HP1010

12" - 700 W - 96 dB

NOMINAL SPECIFICATIONS

Nominal Diameter	300 mm (12 in)
Overall Diameter	316 mm (12.44 in)
Bolt Circle Diameter	298.5 mm (11.75 in)
Baffle Cutout Diameter	282 mm (11.10 in)
Depth	142 mm (5.59 in)
Flange and gasket Thickness	12 mm (0.47 in)
Net Weight	9.22 kg (20.33 lb)
Shipping Box	350 x 346 x 190 mm
(Single Carton Box)	(13.78 x 13.62 x 7.48 in)
Shipping Weight	10 kg (22.05 lb)

TECHNICAL PARAMETERS

Nominal Impedance	8 Ω
Minimum Impedance	7 Ω
AES Power Handling (1)	700 W
Maximum Power Handling (4)	1400 W
Sensitivity (1W/1m)	96 dB
Frequency Range	45 ÷ 3150 Hz
Voice Coil Diameter	100 mm (4 in)
Winding Material	Al
Former Material	Glass Fiber
Winding Depth	22 mm (0.87 in)
Magnetic Gap Depth	10.5 mm (0.41 in)
Flux Density	1.05 T
Magnet	Ferrite Ring
Basket Material	Aluminum
Demodulation	No
Cone Surround (5)	M-Roll
NET Air Volume filled by Loudspeaker	3.3 dm ³ (0.117 ft ³)
Spider Profile	2x non-adjacent symmetrical constant height waves

THIELE & SMALL PARAMETERS

Fs	45 Hz
Re	5.5 Ω
Qes	0.35
Qms	9.4
Qts	0.33
Vas	50 dm ³ (1.77 ft ³)
Sd	496 cm ² (76.9 in ²)
Xmax (2)	9.25 mm
Xdamage (3)	21.9 mm
Mms	87.2 g
Bl	19.8 N/A
Le	1.33 mH
Mmd	80.5 g
Cms	0.14 mm/N
Rms	2.62 kg/s
η _o (Eta Zero)	1.28 %
EBP	129 Hz

NOTE:

- 2 Hours Test According to AES 2-1984 Rev. 2003
- Xmax = [(Winding Depth - magnetic gap depth)/2] + (magnetic gap depth / 3)
- Maximum excursion before permanent damage
- Maximum power is defined as 3dB greater than nominal power
- Treated Polycotton

