

8FE200



8" - 130 W - 95 dB - 8 Ohm

NOMINAL SPECIFICATIONS

| | |
|----------------------------------|---|
| Nominal Diameter | 200 mm (8 in) |
| Overall Diameter | 209.2 mm (8.24 in) |
| Bolt Circle Diameter | 196.9 mm (7.75 in) |
| Baffle Cutout Diameter | 178 mm (7.01 in) |
| Depth | 89 mm (3.50 in) |
| Flange and Gasket Thickness | 8 mm (0.31 in) |
| Net Weight | 2.2 kg (4.7 lb) |
| Shipping Box (Single Carton Box) | 227 x 224 x 113 mm (8.9 x 8.8 x 4.4 in) |
| Shipping Weight | 3 kg (6.6 lb) |

PART NUMBER

| | |
|----------------------------------|----------|
| Faston Terminals - 8 Ohm Version | 02004018 |
|----------------------------------|----------|

NOTES:

- (1) 2 Hours Test According to AES 2-1984 Rev. 2003
- (2) Maximum power is defined as 3dB greater than nominal power.
- (3) Treated Polycotton
- (4) $X_{max} = [(winding\ depth - magnetic\ gap\ depth)/2] + (magnetic\ gap\ depth/3)$
- (5) Maximum excursion before permanent damage

TECHNICAL PARAMETERS

| | |
|--------------------------------------|--|
| Nominal Impedance | 8 Ohm |
| Minimum Impedance | 6.8 Ohm |
| AES Power Handling (1) | 130 W |
| Maximum Power Handling (2) | 260 W |
| Sensitivity (1W/1m) | 95 dB |
| Frequency Range | 60-5000 Hz |
| Voice Coil Diameter | 37 mm (1.46 in) |
| Winding Material | Al |
| Former Material | Kapton |
| Winding Depth | 12 mm (0.47 in) |
| Magnetic Gap Depth | 8 mm (0.31 in) |
| Flux Density | 1 T |
| Magnet | Ferrite Ring |
| Basket Material | Steel |
| Demodulation | No |
| Cone Surround (3) | Triple Roll |
| NET Air Volume filled by Loudspeaker | 0.6 dm ³ (0.021 ft ³) |
| Spider Profile | 1x constant height waves |

THIELE & SMALL PARAMETERS

| | |
|-------------|--|
| Fs | 80 Hz |
| Re | 5.9 Ohm |
| Qes | 0.66 |
| Qms | 13.0 |
| Qts | 0.63 |
| Vas | 16.1 dm ³ (0.57 ft ³) |
| Sd | 209 cm ² (32.44 in ²) |
| Xmax (4) | 4.67 mm |
| Xdamage (5) | 10.4 mm |
| Mms | 15.0 g |
| Bl | 8.2 N/A |
| Le | 0.44 mH |
| Mmd | 11.6 g |
| Cms | 0.26 mm/N |
| Rms | 0.6 kg/s |
| Eta Zero | 1.21 % |
| EBP | 121 Hz |

