



HF20AT

2" - 90 W - 110 dB

NOMINAL SPECIFICATIONS

Throat Diameter	50.8 mm (2 in)
Overall Diameter	130.5 mm (5.14 in)
90° Mounting Holes Diameter (4xM6)	102 mm (4.02 in)
Depth	95 mm (3.74 in)
Net Weight	3.3 kg (7.28 lb)
Shipping Box	185 x 170 x 122 mm
(Single Carton Box)	(7.28 x 6.69 x 4.80 in)
Shipping Weight	3.5 kg (7.72 lb)

TECHNICAL PARAMETERS

Nominal Impedance	8 Ω
Minimum Impedance	7.3 Ω
AES Power above 0.9 kHz (1)	90 W
AES Power above 0.65 kHz (1)	50 W
Maximum Power above 0.9 kHz (2)	180 W
Maximum Power above 0.65 kHz (2)	100 W
Minimum Crossover Frequency (3)	0.9 kHz
Sensitivity (1W/1m) (4)	110 dB
Frequency Range	0.5 ÷ 18 kHz
Voice Coil Diameter	74 mm (2.91 in)
Winding Material	Al
Former Material	Kapton
Diaphragm Material	Titanium
Diaphragm Shape	Dome
Winding Depth	2.35 mm (0.10 in)
Magnetic Gap Depth	2.80 mm (0.11 in)
Flux Density	1.95 T
Magnet	Neodymium Ring
Re	5.6 Ω
Phase Plug Design	Annular
NET Air Volume filled by HF Driver	1.1 dm ³ (0.039 ft ³)

NOTE: Driver Mounted on a 2" 90° x 40° Al horn

(1) 2 Hours Test According to AES 2-1984 Rev. 2003

(2) Maximum power is defined as 3 dB greater than nominal power.

(3) 12 dB/oct or higher slope high-pass filter.

(4) Averaged within the frequency range.

