



# HiFi SERIE

## AMT 23CS-C 1.1


RESISTANCE	NOMINAL 8 OHM
Zo 7.6 OHM • Zmin 7.2 OHM • RE 7.3 OHM	
SENSITIVITY @ 2.83 V	89 dB
FREQUENCY RESPONSE / -6 dB	1300 Hz – 30 kHz
POWER HANDLING	125 W
RESONANCE FREQUENCY / FS	1450 Hz
RECOMMENDED CROSSOVER / 6 dB	3000 Hz
RECOMMENDED CROSSOVER / 12 dB	2500 Hz
DISPERSION HORIZONTAL / 15 kHz / -6 dB	60°
DIAPHRAGM AREA	2210 mm <sup>2</sup>
MAGNET MATERIAL	NEODYMIUM
FACE PLATE	3 mm Anodized Aluminum
TOTAL WEIGHT	480 g
Round Face Plate (-C):	130 mm
Recangular Face Plate (-R):	100 x 100 mm




SPL 2.83 V - Phase - Impedance




SPL HORIZONTAL 0° - 15° - 30°




SPL VERTIKAL 0° - 5° - 15°




Waterfall




Harmonic Distortion 105 dB




Impulse Response



Harmonic Distortion 2.83 V



Harmonic Distortion 105 dB



Step Response