

MB12X351

MID - BASS

DESCRIPTION

The MB12X351 is designed to provide an excellent frequency response linearity with very low distortion.

A very strong neodymium magnetic structure guarantee dynamic and precision, a new and unique 3,5" voice coil design provides a very high power handling, especially recommended in comparison to a standard 3" voice coil. The new dual forced hyper-venting system guarantee a very efficient voice coil ventilation for minimum power compression and incredible power handling.



FEATURES

- 3.5-inch, fiberglass inside/outside copper voice coil
- 1400W continuous program power handling
- 98.5 dB Sensitivity
- 45 Hz 2.5 kHz Frequency range



TECHNICAL SPECIFICATIONS

General specifications	Nominal Diameter:	12 inch / 305 mm
------------------------	-------------------	------------------

Rated Impedance: 8 ohm
Program Power (watt): 1400 W
Power handling capacity: 700 W
Sensitivity: 98.5 dB
Frequency range: 45 - 2500 Hz

Effective piston diameter: 260 mm / 10.24 inch

Max. Excursion Before Damage: 40 mm / 1.57 inch

Minimum Impedance (ohm): 7.1 ohm

Voice Coil Diameter: 3.5 inch / 89 mm

Voice Coil Winding Material: Copper

Voice Coil Length: 19 mm / 0.75 inch

Number of layers: 2

Kind of layers: inside/outside

Top Plate Thickness: 10 mm / 0.39 inch

Cone Design: Curved
Surround Material: Polycotton
Surround Design: M-roll
Magnets: Ceramic
Dual-force air ventilation: Yes

Spider: Dual with silicon based damping control

5.40 ohm

Thiele - small parameters Resonance frequency (Fs): 55 Hz

DC resistance (Re) (ohm):

Mechanical factor: 5.90 Qms Electrical factor: 0.27 Qes Total factor: 0.26 Qts BI factor (BI) (T x m): 22.50 T x m Effective moving mass (Mms): 72.0 g Equivalent Cas air loaded (Vas): 46.0 liters 0.050 m2 Effettive piston area (Sd): Max. linear excursion (Xmax): 7.0 mm Voice coil inductance @ 1kHz (Le1k): 0.90 mH Half-space efficency (Eff): 3 00%

Mounting informations Overall diameter: 320 mm / 12.6 inches

Bolt circle diameter: 293-304 mm / 11.54-11.97 inch

Bolt hole diameter: 7 mm / 0.28 inch
Front mount baffle cut-out: 282 mm / 11.1 inch
Rear mount baffle cut-out: 284 mm / 11.18 inch
Volume occupied by the driver: 2.2 liters / 0.09 ft3

Standard compliance CE marking: Yes

DATASHEET



 Size
 Height:
 143 mm / 5.63 inches

 Diameter:
 320 mm / 12.6 inches

 Weight:
 7.6 kg / 16.76 lbs

 Shipping informations
 Package Height:
 194 mm / 7.64 inches

 Package Width:
 354 mm / 13.94 inches

Package Depth: 364 mm / 14.33 inches
Package Weight: 8.4 kg / 18.52 lbs

PART NUMBER

• 11100100

MB12X351

8ohm









