



TW SERIES

25-669C



1" SILK DOME

- SOFT SILK DOME DIAPHRAGM COATED WITH HIGH LOSS MATERIAL
- FERROFLUID COOLED
- WOOL IN CAVITY OF POLE PIECE
- ABS FRONT PANEL



DIAPHRAGM MTL	Natural silk
SURROUND MTL	N/A
NOMINAL IMPEDANCE	6 W
DCR IMPEDANCE	5.4 W
SENSITIVITY 1W/1m	91 dB
FREQUENCY RESPONSE	1000-25K Hz
FREE AIR RESONANCE	1000 Hz
VOICE COIL DIAMETER	25 mm
AIR GAP HEIGHT	3 mm
RATED POWER INPUT	8 W
MAXIMUM POWER INPUT	80 W
FORCE FACTOR, BL	N/A
MAGNET WEIGHT (7.6 oz)	216 g
MOVING MASS	N/A
FERRO FLUID ENHANCED	Yes
SUSPENSION COMPL.	N/A
EFFEC.PISTON AREA	N/A
Levc	N/A
Zo	N/A
X-max	N/A
Vas	N/A
Qts	N/A
Qms	N/A
Qes	N/A



VOICE: 886.2.26570282 FAX: 886.2.26580166
E-MAIL: info@tb-speaker.com

CLOSE